


FUEL HOSE AND FITTINGS (R5) DOT APPROVED



Hi temperature fuel and diesel SAE100 R5 standards
Single wire inner braid with blue polyester braid cover.
Operating temperature range: -49°C to +150°C


| Dn Size | Size ID | Max Op Press | Min Bend Radius | Part Number |
|---------|---------|--------------|-----------------|-------------|
| -4 | 3/16" | 3000 psi | 3" | FC300-4 |
| -6 | 5/16" | 2250 psi | 4" | FC300-6 |
| -8 | 13/32" | 2000 psi | 4.62" | FC300-8 |
| -12 | 5/8" | 1500 psi | 6.5" | FC300-12 |
| -16 | 7/8" | 1500 psi | 7.38" | FC300-16 |

JIC FEMALE




| Thread | Hose | Part Number |
|--------|-------|-------------|
| 7/16 | 3/16 | 4411-4S |
| 9/16 | 5/16 | 4411-6S |
| 3/4 | 13/32 | 4411-8S |
| 1-1/16 | 5/8 | 4411-12S |
| 1-5/16 | 7/8 | 4411-16S |

JIC FEMALE 90 DEG




| Thread | Hose | Part Number |
|--------|-------|-------------|
| 7/16 | 3/16 | 190296-4S |
| 9/16 | 5/16 | 190261-6S |
| 3/4 | 13/32 | 190296-8S |
| 1-1/16 | 5/8 | 190261-12S |
| 1-5/16 | 7/8 | 190261-16S |

BSPT MALE




| Thread | Hose | Part Number |
|--------|-------|--------------|
| 1/4 | 3/16 | 07.545-4-4 |
| 3/8 | 5/16 | 07.545-6-6 |
| 1/2 | 13/32 | 07.545-8-8 |
| 3/4 | 5/8 | 07.545-12-12 |
| 1" | 7/8 | 07.545-16-16 |

JIC FEMALE 45 DEG




| Thread | Hose | Part Number |
|--------|-------|-------------|
| 7/16 | 3/16 | 190297-4S |
| 9/16 | 5/16 | 190265-6S |
| 3/4 | 13/32 | 190287-8S |
| 1-1/16 | 5/8 | 190265-12S |
| 1-5/16 | 7/8 | 190265-16S |

BSP FEMALE



| Thread | Hose | Part Number |
|--------|-------|--------------|
| 1/4 | 3/16 | 07.421-4-4 |
| 3/8 | 5/16 | 07.421-6-6 |
| 1/2 | 13/32 | 07.421-8-8 |
| 3/4 | 5/8 | 07.421-12-12 |
| 1" | 7/8 | 07.421-16-16 |

BSP FEMALE 90 DEG



| Thread | Hose | Part Number |
|--------|-------|--------------|
| 1/4 | 3/16 | 07.011-4-4 |
| 3/8 | 5/16 | 07.011-6-6 |
| 1/2 | 13/32 | 07.11-8-8 |
| 3/4 | 5/8 | 07.011-12-12 |
| 1" | 7/8 | 07.011-16-16 |

PUSH FIT HOSE AND FITTINGS - LOW PRESSURE



Low pressure push-in
Single fabric braid synthetic rubber tube
Operating temperature range: -40°C to +100°C


| Dn Size | Size ID | Max Op Press | Min Bend Radius | Part Number |
|---------|---------|--------------|-----------------|-------------|
| -4 | 1/4" | 360 psi | 3" | D600-4 |
| -6 | 3/8" | 300 psi | 4" | D600-6 |
| -8 | 1/2" | 300 psi | 5" | D600-8 |

JIC FEMALE



| Thread | Hose | Part Number |
|--------|------|-------------|
| 7/16 | 1/4 | 4797-4B |
| 9/16 | 3/8 | 4741-6B |
| 3/4 | 1/2 | 4797-8B |

JIC FEMALE 90 DEG




| Thread | Hose | Part Number |
|--------|------|-------------|
| 7/16 | 1/4 | 191321-4S |
| 9/16 | 3/8 | 190516-6S |
| 3/4 | 1/2 | 191321-8S |

BSPT MALE



| Thread | Hose | Part Number |
|--------|------|-------------|
| 1/8 | 1/4 | 351-2-4 |
| 1/4 | 1/4 | 351-4 |
| 3/8 | 3/8 | 351-6 |
| 1/2 | 1/2 | 351-8 |

NPT MALE




| Thread | Hose | Part Number |
|--------|------|-------------|
| 1/8 | 1/4 | 4738-2-4B |
| 1/4 | 1/4 | 4738-4-4B |
| 3/8 | 3/8 | 4738-6-6B |
| 1/2 | 1/2 | 4738-8-8B |

BSP FEMALE



| Thread | Hose | Part Number |
|--------|------|-------------|
| 1/4 | 1/4 | 07.390-4-4 |
| 3/8 | 3/8 | 07.390-6-6 |
| 1/2 | 1/2 | 07.390-8-8 |

BSP FEMALE 90 DEG



| Thread | Hose | Part Number |
|--------|------|-------------|
| 1/4 | 1/4 | 07.140-4-4 |
| 3/8 | 3/8 | 07.140-6-6 |
| 1/2 | 1/2 | 07.140-8-8 |